




Notes	
	Yorkstone paving: specification and laying pattern to match existing. Paving to be laid on a mortar bed. Refer to Detail and Section drawings
	Marshalls tegula concrete sett paving or similar, laid to match existing Specification: 'Tegula Multi pack' (120x160/160x160/160x240) Depth: 80mm, Colour: Traditional Refer to Detail and Section drawings
	Large reclaimed cobbles to match existing sandstone or gristone cobbles. Laid to patterns shown. Specification: Reclaimed cobbles to match existing Random size, nominally 250 x 200 x 250mm. Refer to Detail and Section drawings
	Shrub and perennial planting: Refer to planting plan ????
	Tactile paving: Red Granite, blister pattern. Size 400mm x 400mm x 50mm (min) Tactile paving must comply with the DETR's Guidance on the use of Tactile Paving Surfaces' and the Department for Transport's Interim changes to the Guidance on the use of Tactile Paving Surfaces'
	Tactile paving: Yellow Granite, blister pattern. Size 400mm x 400mm x 50mm (min) Tactile paving must comply with the DETR's Guidance on the use of Tactile Paving Surfaces' and the Department for Transport's Interim changes to the Guidance on the use of Tactile Paving Surfaces'
	Tactile paving: Grey Granite, blister pattern. Size 400mm x 400mm x 50mm (min) Tactile paving must comply with the DETR's Guidance on the use of Tactile Paving Surfaces' and the Department for Transport's Interim changes to the Guidance on the use of Tactile Paving Surfaces'
	Tactile paving: Red Granite, corduroy pattern. Size 400mm x 400mm x 50mm (min) Tactile paving must comply with the DETR's Guidance on the use of Tactile Paving Surfaces' and the Department for Transport's Interim changes to the Guidance on the use of Tactile Paving Surfaces'
	Yorkstone separation / delineation strip: specification to match existing and proposed Yorkstone paving. Paving to be laid on a mortar bed. Dimensions: (W x L x D): 200mm x Length x 65mm Refer to Detail and Section drawings
	Reclaimed stone steps to be used as separation / delineation strips Steps to be laid on a S72 concrete bed, with S72 concrete haunching. Reclaimed stone steps located in the Town Hall's rear car park. Refer to Detail and Section drawings
	Resin bound surfacing, laid over a 50mm binder course of AC14 open textured bitmac and 150mm layer of compacted sub-base.
	Additional area of Resin bound surfacing, laid over a 50mm binder course of AC14 open textured bitmac and 150mm layer of compacted sub-base.
	Yorkstone paving: specification and to match existing. Paving pattern as shown. Paving to be laid on a mortar bed.
	Proposed tree planting: Underground geying Refer to detail drawings
	Proposed tree planting: Double staked Refer to detail drawings
	Existing tree
	Proposed up-lighter for the trees. Allow for the supply and installation of the up lighters (Specification to follow) and all electrical connections, including timers and metering.
	Proposed tegulae: (600 x 600 x 65mm) artistic Yorkstone paving slabs. Allow for the supply and installation of artistic slabs laid on a mortar bed

Date	Revision



Fylde Council

Technical Services
Development Services
The Town Hall
Lytham St Annes
Lancashire
FY8 1LW
Tel: 01253 658658 E-mail: webmaster@fylde.gov.uk

Drawn By:	Date:
SK	Jan 2020
Checked By:	Scale:
PD	1:500 @ A1
Project:	
St Annes Pier Link	
Title:	
General Arrangement	
Drawing Number:	
RT - 19005/01/Rev0	